

SPECIFICATION FOR ACTIVE 350GSM MAINTENANCE PADS

	1.14

	HMP5
Size	40cm x 52cm
Perforations	Along at 26cm
Colour	Grey
Pack Quantity	100
Pack Wt (gross)	7.3 kg
Pack Size	40 x 52 x 40 cm
Sorbency (pack)	88 - 133 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using water. Higher figure based on high viscosity liquid with no drain.

Composition:	>99.5% Polypropylene, <0.5% dye Meltblown, ultrasonically bonded
Basis Wt:	350gsm
Pack Type:	Bag
Compatibility:	May be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, <i>with the exception of strong oxidising agents</i> . Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
Fire Resistance:	Good. (Physically flame-retardant) Incinerable to zero ash.
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
Safety Data:	Refer to our Safety Data Sheet. This product is non-toxic to users and to aquatic life. Further technical advice is available if required.
Note:	All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018